

EPODUX IM 213 BASE - G000633PY

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : EPODUX IM 213 BASE
Product code : G000633PY.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paint, coating or ancillary activities.

1.3. Details of the supplier of the safety data sheet

Registered company name : PEINTURES MAESTRIA.
Address : ZI - Rue Denis Papin.09100.PAMIER.S.FRANCE.
Telephone : +33 5 61 67 97 40. Fax : +33 5 61 69 75 71.
labo-fds@maestria.fr

1.4. Emergency telephone number : 01 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin irritation, Category 2 (Skin Irrit. 2, H315).
Eye irritation, Category 2 (Eye Irrit. 2, H319).
Skin sensitisation, Category 1 (Skin Sens. 1, H317).
Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).
This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS09



GHS07

Signal Word :

WARNING

Product identifiers :

EC 216-823-5
603-103-00-4

SOLVANT NAPHTA AROMATIQUE LEGER (PETROLE)
OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS.

Additional labeling :

EUH205
EUH211

Contains epoxy constituents. May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Hazard statements :

H315
H317
H319
H411

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

EPODUX IM 213 BASE - G000633PY

Precautionary statements - Prevention :

P260	Do not breathe dust / mist / vapors / spray.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection

Precautionary statements - Response :

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) \geq 0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances \geq 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	Classification (EC) 1272/2008	Note	%
CAS: 1675-54-3 EC: 216-823-5 REACH: 01-2119456619-26 SOLVANT NAPHTA AROMATIQUE LEGER (PETROLE)	GHS07, GHS09 Wng Skin Irrit. 2, H315 Skin Sens. 1B, H317 Eye Irrit. 2, H319 Aquatic Chronic 2, H411		25 \leq x % < 50
INDEX: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5 TITANIUM DIOXIDE [IN POWDER FORM CONTAINING 1 % OR MORE OF PARTICLES WITH AERODYNAMIC DIAMETER \leq 10 μ M]	GHS08 Wng Carc. 2, H351	[1] [10]	10 \leq x % < 25
INDEX: 603-103-00-4 CAS: 68609-97-2 EC: 271-846-8 REACH: 01-2119485289-22 OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS.	GHS07 Wng Skin Irrit. 2, H315 Skin Sens. 1, H317		2.5 \leq x % < 10
CAS: 95-47-6 EC: 202-422-2 REACH: 01-2119485822-30 O-XYLENE	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 Aquatic Chronic 3, H412	[1]	2.5 \leq x % < 10
EC: 918-668-5 REACH: 01-2119455851-35 SOLVANT NAPHTA, PETROLEUM	GHS09, GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH:066		0 \leq x % < 2.5

EPODUX IM 213 BASE - G000633PY

INDEX: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 REACH: 01-2119457558-25 PROPAN-2-OL	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]	0 <= x % < 2.5
--	--	-----	----------------

Specific concentration limits:

Identification	Specific concentration limits	ATE
CAS: 95-47-6 EC: 202-422-2 REACH: 01-2119485822-30 O-XYLENE		inhalation: ATE = 4595 mg/l 4h (gas) oral: ATE = 3567 mg/kg BW

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter <= 10 µm.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

EPODUX IM 213 BASE - G000633PY

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

Do not discharge fire extinguishing water into the environment.

In case of fire can produce carbon monoxide, aldehydes, acids and mixtures of organic compounds unidentified.

5.3. Advice for firefighters

Protective clothing and breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

EPODUX IM 213 BASE - G000633PY

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
95-47-6	221	50	442	100	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
13463-67-7	10 mg/m3			A4	
95-47-6	100 ppm	150 ppm		A4; BEI	
67-63-0	200 ppm	400 ppm		A4; BEI	

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
13463-67-7	-	10	-	-	-	-
95-47-6	50	221	100	442	*	4 Bis. 84. *
67-63-0	-	-	400	980	-	84

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
13463-67-7	4 mg/m ³				
95-47-6	50 ppm	100 ppm	-	-	-
67-63-0	400 ppm 999 mg/m ³	500 ppm 1250 mg/m ³			

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Particle filter according to standard EN143 :

- P2 (White)

EPODUX IM 213 BASE - G000633PY

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****Physical state**

Physical state : Viscous liquid.

Colour

Unspecified

Odour

Odour threshold : Not stated.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not relevant.

Flammability

Flammability (solid, gas) : Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) Not stated.

:

Explosive properties, upper explosivity limit (%) Not stated.

:

Flash pointFlash Point Interval : $60^{\circ}\text{C} < \text{FP} \leq 93^{\circ}\text{C}$ **Auto-ignition temperature**

Self-ignition temperature : Not relevant.

Decomposition temperature

Decomposition point/decomposition range : Not relevant.

pH

pH (aqueous solution) : Not stated.

pH : Not relevant.

Kinematic viscosity

Viscosity : Not stated.

Solubility

Water solubility : Insoluble.

Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density and/or relative densityDensity : > 1 **Relative vapour density**

Vapour density : Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

EPODUX IM 213 BASE - G000633PY

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

May cause an allergic reaction by skin contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and a respiratory tract sensitiser as well as an irritant.

Constituents with a low molecular weight irritate the eyes, mucous membranes and the skin

Repeated contact with the skin may cause irritation and hypersensitisation, possibly in combination with other epoxide compounds.

11.1.1. Substances**Acute toxicity :**

O-XYLENE (CAS: 95-47-6)

Oral route :

LD50 = 3567 mg/kg bodyweight/day

Species : Rat

Inhalation route (Gas) :

LC50 = 4595 ppm

Species : Mouse

Duration of exposure : 4 h

11.1.2. Mixture**Respiratory or skin sensitisation :**

Contains epoxy compounds. May cause an allergic reaction.

11.2. Information on other hazards**SECTION 12 : ECOLOGICAL INFORMATION**

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity**12.1.1. Substances**

O-XYLENE (CAS: 95-47-6)

Fish toxicity :

LC50 = 7.6 mg/l

Species : *Oncorhynchus mykiss*

Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 3.82 mg/l

Species : *Daphnia magna*

Duration of exposure : 48 h

EPODUX IM 213 BASE - G000633PY

Algae toxicity :

ECr50 = 4.7 mg/l
Species : Pseudokirchnerella subcapitata
Duration of exposure : 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

O-XYLENE (CAS: 95-47-6)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

12.3.1. Substances

O-XYLENE (CAS: 95-47-6)

Octanol/water partition coefficient :

log K_{ow} = 3.12

Bioaccumulation :

BCF = 14.13

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

08 01 11 * waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

14.1. UN number or ID number

3082

14.2. UN proper shipping name

UN3082=ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(solvant naphta aromatique leger (petrole))

EPODUX IM 213 BASE - G000633PY

14.3. Transport hazard class(es)

- Classification :



9

14.4. Packing group

III

14.5. Environmental hazards

- Environmentally hazardous material :

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	9	M6	III	9	90	5 L	274 335 375 601	E1	3	-

Not subject to this regulation if Q <= 5 l / 5 kg (ADR 3.3.1 - DS 375)

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	9	-	III	5 L	F-A, S-F	274 335 969	E1	Category A	-

Not subject to this regulation if Q <= 5 l / 5 kg (IMDG 3.3.1 - 2.10.2.7)

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	9	-	III	964	450 L	964	450 L	A97 A158 A197 A215	E1
	9	-	III	Y964	30 kg G	-	-	A97 A158 A197 A215	E1

Not subject to this regulation if Q <= 5 l / 5 kg (IATA 4.4.4 - DS A197)

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

Marine pollutant (IMDG 3.1.2.9):(solvant naphta aromatique leger (petrole))

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

Container information:The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):
<https://echa.europa.eu/substances-restricted-under-reach>.**Particular provisions :**

No data available.

15.2. Chemical safety assessment

No data available.

EPODUX IM 213 BASE - G000633PY**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer .
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS07 : Exclamation mark

GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.

EPODUX IM 213 DURCISSEUR - G002406PY**SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1. Product identifier**

Product name : EPODUX IM 213 DURCISSEUR

Product code : G002406PY.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paint, coating or ancilliary activities.

1.3. Details of the supplier of the safety data sheet

Registered company name : PEINTURES MAESTRIA.

Address : ZI - Rue Denis Papin.09100.PAMIERS.FRANCE.

Telephone : +33 5 61 67 97 40. Fax : +33 5 61 69 75 71.

labo-fds@maestria.fr

1.4. Emergency telephone number : 01 45 42 59 59.Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.**SECTION 2 : HAZARDS IDENTIFICATION****2.1. Classification of the substance or mixture****In compliance with EC regulation No. 1272/2008 and its amendments.**

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).

Acute inhalation toxicity, Category 4 (Acute Tox. 4, H332).

Skin corrosion, Category 1 (Skin Corr. 1, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Acute hazard, Category 1 (Aquatic Acute 1, H400).

Hazardous to the aquatic environment - Chronic hazard, Category 1 (Aquatic Chronic 1, H410).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05



GHS09



GHS07

Signal Word :

DANGER

Product identifiers :

EC 202-859-9

ALCOOL BENZYLIQUE

EC 216-032-5

M-PHENYLENEBIS(METHYLAMINE)

EC 203-680-9

3-AMINOPROPYLDIMETHYLAMINE

EC 202-013-9

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

EC 217-164-6

N-(3-(TRIMETHOXSILYL)PROPYL)ETHYLENEDIAMINE

EC 292-587-7

AMINES, POLYETHYLENEPOLY-, FRACTION TETRAETHYLENEPENTAMINE

EC 292-588-2

3,6-DIAZAOCTANE-1,8-DIAMINE

Additional labeling :

EPODUX IM 213 DURCISSEUR - G002406PY

Hazard statements :

H302 + H332	Harmful if swallowed or if inhaled.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statements - Prevention :

P260	Do not breathe dust / mist / vapors / spray.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection

Precautionary statements - Response :

P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European CHemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	Classification (EC) 1272/2008	Note	%
CAS: 100-51-6 EC: 202-859-9 REACH: 01-2119492630-38 ALCOOL BENZYLIQUE	GHS07 Wng Acute Tox. 4, H302 Eye Irrit. 2, H319 Acute Tox. 4, H332		25 \leq x % < 50
CAS: 106906-26-7 FATTY ACIDS, C18-UNSATD., DIMERS, POLYMERS WITH BISPHENOLA, EPICHLOROHYDRIN, TALL-OIL FATTY ACIDS, TETRAETHYLENEPENTAMINE AND TRIETHYLENETETRAMINE	GHS09 Wng Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 1		25 \leq x % < 50
CAS: 1477-55-0 EC: 216-032-5 REACH: 01-2119480150-50 M-PHENYLENEBIS(METHYLAMINE)	GHS07, GHS05 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1B, H317 Eye Dam. 1, H318 Acute Tox. 4, H332 Aquatic Chronic 3, H412 EUH:071	[1]	10 \leq x % < 25
CAS: 109-55-7 EC: 203-680-9 REACH: 01-2119486842-27 3-AMINOPROPYLDIMETHYLAMINE	GHS07, GHS05, GHS02 Dgr Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1B, H317 Eye Dam. 1, H318 STOT SE 3, H335		2.5 \leq x % < 10

EPODUX IM 213 DURCISSEUR - G002406PY

CAS: 90-72-2 EC: 202-013-9 REACH: 01-2119560597-27 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHE NOL	GHS07, GHS05 Dgr Acute Tox. 4, H302 Skin Corr. 1, H314 Eye Dam. 1, H318		2.5 <= x % < 10
CAS: 1760-24-3 EC: 217-164-6 REACH: 01-2119970215-39 N-(3-(TRIMETHOXYSYLYL)PROPYL)ETHYL ENEDIAMINE	GHS05, GHS07 Dgr Skin Sens. 1, H317 Eye Dam. 1, H318 STOT SE 3, H335		0 <= x % < 2.5
CAS: 90640-66-7 EC: 292-587-7 REACH: 01-2119487290-37 AMINES, POLYETHYLENEPOLY-, FRACTION TETRAETHYLENEPENTAMINE	GHS07, GHS05, GHS09, GHS08 Dgr Acute Tox. 4, H302 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		0 <= x % < 2.5
CAS: 90640-67-8 EC: 292-588-2 REACH: 01-2119487919-13 3,6-DIAZAOCTANE-1,8-DIAMINE	GHS07, GHS05 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 3, H412		0 <= x % < 2.5

Specific concentration limits:

Identification	Specific concentration limits	ATE
CAS: 1477-55-0 EC: 216-032-5 REACH: 01-2119480150-50 M-PHENYLENEBIS(METHYLAMINE)		inhalation: ATE = 1.16 mg/1 4h (dust/mist) oral: ATE = 930 mg/kg BW
CAS: 90640-66-7 EC: 292-587-7 REACH: 01-2119487290-37 AMINES, POLYETHYLENEPOLY-, FRACTION TETRAETHYLENEPENTAMINE		dermal: ATE = 1260 mg/kg BW oral: ATE = 1716.2 mg/kg BW
CAS: 90640-67-8 EC: 292-588-2 REACH: 01-2119487919-13 3,6-DIAZAOCTANE-1,8-DIAMINE		dermal: ATE = 1465 mg/kg BW oral: ATE = 1716 mg/kg BW

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures**In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Do not proceed with mouth-to-mouth or mouth-to-nose resuscitation. Use the appropriate equipment.

In the event of inhalation of spray mist, seek medical attention immediately, showing the packaging or label.

EPODUX IM 213 DURCISSEUR - G002406PY

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.
Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.
Remove any soiled or splashed clothing immediately.
Watch out for any remaining product between skin and clothing, watches, shoes, etc.
In the event of an allergic reaction, seek medical attention.
If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.
In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.
Keep the person exposed at rest. Do not force vomiting.
Seek medical attention immediately, showing the label.
If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.
If swallowed, if the quantity is small (not more than one mouthful), rinse the mouth with water and consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)
- water with AFFF (Aqueous Film Forming Foam) additive
- halon

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.
Do not breathe in smoke.
In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid inhaling the vapors.
Avoid any contact with the skin and eyes.
If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

EPODUX IM 213 DURCISSEUR - G002406PY**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1477-55-0			0.1 mg/m3	Skin	

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
1477-55-0	-	-	-	0.1	-	-

EPODUX IM 213 DURCISSEUR - G002406PY**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

AMINES, POLYETHYLENEPOLY-, FRACTION TETRAETHYLENEPENTAMINE (CAS: 90640-66-7)

Final use:	Workers.
Exposure method:	Dermal contact.
Potential health effects:	Long term local effects.
DNEL :	0.25 mg of substance/cm2
Final use:	Consumers.
Exposure method:	Ingestion.
Potential health effects:	Long term systemic effects.
DNEL :	0.21 mg/kg body weight/day
Exposure method:	Dermal contact.
Potential health effects:	Long term local effects.
DNEL :	20.8 µg of substance/cm2
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	0.14 mg of substance/m3
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	0.82 mg of substance/m3

M-PHENYLENEBIS(METHYLAMINE) (CAS: 1477-55-0)

Final use:	Workers.
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	0.33 mg/kg body weight/day
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	1.2 mg of substance/m3
Exposure method:	Inhalation.
Potential health effects:	Long term local effects.
DNEL :	0.2 mg of substance/m3

Predicted no effect concentration (PNEC):

AMINES, POLYETHYLENEPOLY-, FRACTION TETRAETHYLENEPENTAMINE (CAS: 90640-66-7)

Environmental compartment:	Soil.
PNEC :	2.5 mg/kg
Environmental compartment:	Fresh water.
PNEC :	0.01 mg/l
Environmental compartment:	Sea water.
PNEC :	0.001 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	3.198 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0.32 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	4.6 mg/l

M-PHENYLENEBIS(METHYLAMINE) (CAS: 1477-55-0)

EPODUX IM 213 DURCISSEUR - G002406PY

Environmental compartment: PNEC :	Soil. 0.045 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.094 mg/l
Environmental compartment: PNEC :	Sea water. 0.009 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.43 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.043 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 10 mg/l

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

Wear suitable protective clothing and, in particular, an apron and boots. These items of clothing shall be maintained in good condition and cleaned after use.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Particle filter according to standard EN143 :

- P2 (White)

EPODUX IM 213 DURCISSEUR - G002406PY

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****Physical state**

Physical state : Viscous liquid.

Colour

Unspecified

Odour

Odour threshold : Not stated.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not relevant.

Flammability

Flammability (solid, gas) : Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) Not stated.

:

Explosive properties, upper explosivity limit (%) Not stated.

:

Flash pointFlash Point Interval : $93^{\circ}\text{C} < \text{FP} \leq 100^{\circ}\text{C}$ **Auto-ignition temperature**

Self-ignition temperature : Not relevant.

Decomposition temperature

Decomposition point/decomposition range : Not relevant.

pH

pH (aqueous solution) : Not stated.

pH : Not relevant.

Kinematic viscosity

Viscosity : Not stated.

Solubility

Water solubility : Insoluble.

Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density and/or relative densityDensity : > 1 **Relative vapour density**

Vapour density : Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

EPODUX IM 213 DURCISSEUR - G002406PY**10.3. Possibility of hazardous reactions**

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Harmful if swallowed.

Harmful by inhalation.

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May cause an allergic reaction by skin contact.

11.1.1. Substances**Acute toxicity :**

3,6-DIAZAOCANE-1,8-DIAMINE (CAS: 90640-67-8)

Oral route : LD50 = 1716 mg/kg bodyweight/day
Species : Rat

Dermal route : LD50 = 1465 mg/kg bodyweight/day
Species : Rabbit

AMINES, POLYETHYLENEPOLY-, FRACTION TETRAETHYLENEPENTAMINE (CAS: 90640-66-7)

Oral route : LD50 = 1716.2 mg/kg bodyweight/day
Species : Rat

Dermal route : LD50 = 1260 mg/kg bodyweight/day
Species : Rabbit

M-PHENYLENEBIS(METHYLAMINE) (CAS: 1477-55-0)

Oral route : LD50 = 930 mg/kg bodyweight/day
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 3100 mg/kg bodyweight/day
Species : Rat

Inhalation route (Dusts/mist) : LC50 = 1.16 mg/l
Species : Rat
OECD Guideline 403 (Acute Inhalation Toxicity)

EPODUX IM 213 DURCISSEUR - G002406PY

Duration of exposure : 4 h

11.1.2. Mixture

No toxicological data available for the mixture.

11.2. Information on other hazards**SECTION 12 : ECOLOGICAL INFORMATION**

Very toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity**12.1.1. Substances**

3,6-DIAZAOCTANE-1,8-DIAMINE (CAS: 90640-67-8)

Fish toxicity : LC50 = 330 mg/l
Duration of exposure : 96 hCrustacean toxicity : EC50 = 31.1 mg/l
Species : Daphnia magna
Duration of exposure : 48 hAlgae toxicity : ECr50 = 20 mg/l
Duration of exposure : 72 h

M-PHENYLENEBIS(METHYLAMINE) (CAS: 1477-55-0)

Fish toxicity : LC50 = 87.6 mg/l
Species : Oryzias latipes
Duration of exposure : 96 h
OECD Guideline 203 (Fish, Acute Toxicity Test)Crustacean toxicity : EC50 = 35.1 mg/l
Species : Daphnia magna
Duration of exposure : 24 h
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)EC50 mg/l
Species : Daphnia magna
Duration of exposure : 21 days
OECD Guideline 211 (Daphnia magna Reproduction Test)NOEC = 4.7 mg/l
Species : Daphnia magna
Duration of exposure : 21 days
OECD Guideline 211 (Daphnia magna Reproduction Test)Algae toxicity : ECr50 = 33.3 mg/l
Species : Pseudokirchnerella subcapitata
Duration of exposure : 72 h
OECD Guideline 201 (Alga, Growth Inhibition Test)NOEC = 10.5 mg/l
Species : Pseudokirchnerella subcapitata
Duration of exposure : 72 h
OECD Guideline 201 (Alga, Growth Inhibition Test)**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability**12.2.1. Substances**

3,6-DIAZAOCTANE-1,8-DIAMINE (CAS: 90640-67-8)

EPODUX IM 213 DURCISSEUR - G002406PY

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

AMINES, POLYETHYLENEPOLY-, FRACTION TETRAETHYLENEPENTAMINE (CAS: 90640-66-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

M-PHENYLENEBIS(METHYLAMINE) (CAS: 1477-55-0)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential**12.3.1. Substances**

M-PHENYLENEBIS(METHYLAMINE) (CAS: 1477-55-0)

Octanol/water partition coefficient : log K_{ow} = 0.18
OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

08 01 11 * waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

14.1. UN number or ID number

3066

14.2. UN proper shipping name

UN3066=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)

- Classification :



8

EPODUX IM 213 DURCISSEUR - G002406PY

14.4. Packing group

II

14.5. Environmental hazards

- Environmentally hazardous material :

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C9	II	8	80	1 L	163 367	E2	2	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	8	-	II	1 L	F-A. S-B	163 367	E2	Category B SW2	-

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	8	-	II	851	1 L	855	30 L	A3 A72 A192 A803	E2
	8	-	II	Y840	0.5 L	-	-	A3 A72 A192 A803	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

Marine pollutant (IMDG 3.1.2.9):(fatty acids, c18-unsatd., dimers, polymers with bisphenol a, epichlorohydrin, tall-oil fatty acids, tetraethylenepentamine and triethylenetetramine)

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

Container information:The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):
<https://echa.europa.eu/substances-restricted-under-reach>.**Particular provisions :**

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

EPODUX IM 213 DURCISSEUR - G002406PY

H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.
LC50 : The concentration of a test substance resulting in 50% lethality in a given period.
EC50 : The effective concentration of substance that causes 50% of the maximum response.
ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.
NOEC : The concentration with no observed effect.
REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.
ATE : Acute Toxicity Estimate
BW : Body Weight
DNEL : Derived No-Effect Level
PNEC : Predicted No-Effect Concentration
STEL : Short-term exposure limit
TWA : Time Weighted Averages
TMP : French Occupational Illness table
TLV : Threshold Limit Value (exposure)
AEV : Average Exposure Value.
ADR : European agreement concerning the international carriage of dangerous goods by Road.
IMDG : International Maritime Dangerous Goods.
IATA : International Air Transport Association.
ICAO : International Civil Aviation Organisation
RID : Regulations concerning the International carriage of Dangerous goods by rail.
WGK : Wassergefährdungsklasse (Water Hazard Class).
GHS05 : Corrosion
GHS07 : Exclamation mark
GHS09 : Environment
PBT: Persistent, bioaccumulable and toxic.
vPvB : Very persistent, very bioaccumulable.
SVHC : Substances of very high concern.